



Sales Director: Darcy
Whatsapp: 008613425174299
Email: Darcy@szledworld.com

Rental indoor led display (576x576 cabinet)



Cabinets:



Cabinet-1,2 side locks



Cabinet-2,1 side lock



Cabinet-3

Features:

- High resolution high precision;
- High contrast,ideal gray scale,presenting the clear and bright pictures
- Large view angle
- The most effective solution for indoor HD billboard.
- Easy to install: No tool needed during installation
- Light weight



Evenness



Noiseless



Beautiful



Good ventilation



Ultra-light



Easy installation

Application:

- Stage Performance Conference Celebration banquet exhibition

Technical Specifications:

Technical indexes	Specification	Specification
Pixel pitch	3mm	6mm
Module size	192mm×192mm	192mm X 192mm
Module resolution	64×64	32 X 32
Module density	11111dots/sqm	27777dots/m2
Cabinet Size(mm)	576x576x80	576x576x80
Pixel configuration	1R1G1B	1R1G1B
Red wavelength	625±2nm	625±2nm
Green wavelength	525±2nm	525±2nm
Blue wavelength	470±2nm	470±2nm
Colors	16777216	16777216
Best viewing distance	3m---15m	≥6m
Horizontal viewing angle	140°	140°
Vertical viewing angle	120°	120°
Maximum power consumption	900W/sqm	1200W/sqm
Average power consumption	300W/sqm	600W/m 2
Brightness	1200cd/m2	2200-3500cd /m 2
Gray scale	16bits of per color	16bits per color
Driving method	1/32 scanning	1/8 or 1/16 scanning
Frame frequency	60Hz	60Hz
Refresh frequency	≥1920 Hz	1920 Hz
Working voltage	AC220V/110V±10%	AC220V/110V±10%
IP grade	IP20-45	IP20-45
Working temperature	-20°C~80°C	-20°C~80°C
MTBF	More than 10,000 hours	More than 10,000 hours
Life span	More than 100,000hours	More than 100,000hours

Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to Led World.