

Taxi LED display



Features:

- Lower Power Consumption;
- 3G/4G/wifi with GPS solution to control all taxi topper signs Clustermanagement in control center;
- High refresh rate, Wide view angle with real pixel RGB, good performance;
- Easy to mounted on the car or taxi top with bracket or belt;
- Can for two sides led displays .



Application:

○ Taxi advertising

Technical Specifications:

Showing content area	W768mm*H256mm	W960mm*H320mm	W960mm*H384mm
Control Type	USB/WIFI/3G/4G asynchronous control		
Pixel pitch	4mm	5mm	6mm
Software(eg.win7,linux)	Window xp /Vista/ win7 (The control system software we provide)		
Resolution	62,500 pixels/sq.m	40,000 pixels/sq.m	27,777 pixels/sq.m
Cabinet material	Aluminum Alloy		
Cabinet color	Silver or Back, depends on customer's requirement		
Cabinet weight	18kg	17kg	21kg
Brightness(cd)	5000cd/sq.m	5000cd/sq.m	5000cd/sq.m
Protection grades	Front IP65/ Back IP65		
Work temperature(°C)	-20 degree C_60 degree C		
Humidity(RH)	10%~90%		
Life span	100000 hours		
Input voltage	12v		
Output voltage	5v		
Power consumption(Ave.)	270W		
Power consumption(Max.)	540W		
Accepting format	AVI,WMV,MPG,MOV,DAT,VOB,MP4,FLV,GIF,SWF,BMP,JPG,GIF,WMF,ICO,TXT,RFT		
Warranty time	2years		
Notes: Specifications are for reference only. Please contact our salesperson for details. All rights are reserved to Led World.			